

PRODUCT DATASHEET

ET-PARROT 105/220...240 I

ET-PARROT | Electronic transformers for low-voltage halogen lamps



AREAS OF APPLICATION

- Effect and accent lighting
- Living rooms
- Object lighting
- Conference rooms
- Restaurants
- Recessed and surface-mounted furniture luminaires
- Shop lighting
- Event rooms

PRODUCT FAMILY BENEFITS

- Very low power loss thanks to high efficacy
- Protective operation throughout the entire partial-load range for long lamp life

PRODUCT FAMILY FEATURES

- Line frequency: 50...60 Hz
- RI suppression: to EN 55015 (A1: 2007)/CISPR 15, EN 55022
- Line harmonics according to EN 61000-3-2
- Immunity according to EN 61547
- Energy efficiency: ≥ 91 % (according to ErP regulation 2012/1194/EC)
- Safety: to EN 61347
- Short-circuit protection, overload protection, overtemperature protection: electronically reversible
- Electrical isolation between the primary side and the secondary side
- Dimmable on the leading edge and trailing edge

TECHNICAL DATA

Electrical data

Lamp wattage	35...105 W
Line current	0.45 A ¹⁾
Power factor λ	0.95 ²⁾
Operating frequency	40 kHz ³⁾
Nominal output voltage	11.5 V ⁴⁾
Nominal voltage	220...240 V
Input voltage AC	198...264 V
Mains frequency	50...60 Hz
System wattage [AGGR]	111.00 W
Input voltage range	220...240 V
Max. ECG no. on circuit breaker 10 A (B)	23
Max. ECG no. on circuit breaker 16 A (B)	38
ECG efficiency	95 % ⁵⁾
Galvanic isolation primary/secondary	4.00 kV ⁶⁾
Inrush current	0.5 A

1) Effectively

2) Minimum


3) Approximately

4) 105 W / 35 W

5) At full load

6) eff

Dimensions & weight



Length	128.0 mm
Width	38.0 mm
Height	31.0 mm
Mounting hole spacing, length	119.0 mm
Cable cross-section, input side	0.75 mm ²

Cable cross-section, output side	0.75 mm ²
Wire preparation length, input side	12 / 6.0 mm ¹⁾
Wire preparation length, output side	12 / 6.0 mm ¹⁾
Product weight	130.00 g

¹⁾ Cable sheath / Wire

Temperatures & operating conditions

Ambient temperature range	0...+40 °C
Maximum temperature at tc test point	85 °C

Additional product data

Design / version	Compact
-------------------------	---------





Capabilities




Dimming method	Trailing-edge phase control
Overload protection	Reversible
Overheating protection	Automatic reversible
Short-circuit protection	Automatic reversible
Max. cable length to lamp/LED module	2.0 m
Cable/wire types, input side	H03VV-F 2x0.75 mm ²
Cable/wire types, output side	H03VV-F 2x0.75 mm ²
Dimmable	Yes
Dimming range	0...100 %
No-load proof	Yes
Suitable for fixtures with prot. class	II

Certificates & standards

Approval marks – approval	C-Tick / CE
Standards	Acc. to EN 55015:2006 + A1:2007/Acc. to EN 61000-3-2/Acc. to EN 61547/Acc. to EN 61347
Type of protection	IP20

DOWNLOAD DATA

File	
 Product Datasheet 321724_ATI ET-PARROT 105220-240 I ATI ET-PARROT 70220-240 I (G+GB)	
 Certificates 504206_VDE-EMC-Certificate ET-PARROT	
 Certificates 504178_EAC HT family	
 Declarations of conformity 710835_EC-DOC Halotronic	

	Declarations of conformity HALTORONIC CE 3674444 210120
	On-Pack-Info 590730_EAC - ET-PARROT ET-ZE
	CAD data 343999_ET-PARROT FILE STP

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321111579	Unpacked 1	122 mm x 35 mm x 28 mm	130.00 g	0.12 dm ³
4008321111586	Shipping carton box 50	290 mm x 206 mm x 220 mm	6971.25 g	13.14 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.