


72109 HLDR-GX5.3

Light source fitting

5905339721099



GENERAL DATA:

Colour: grey

TECHNICAL DATA:

Rated voltage [V]: 24 AC; 24 DC

Rated current [A]: 5

Cap: Gx5,3

Connection type: Free cable ends

Type: Gx5,3

IP class: 00

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 100

Number of units in the secondary packaging: 100

Number of units in the packaging: 2000

Net unit weight [g]: 6

Grammage [g]: 6.25

Length of a unit pack [cm]: 2

Width of a unit pack [cm]: 2

Height of a unit pack [cm]: 12

Weight of a cardboard box [kg]: 12.5

Width of a cardboard box [cm]: 28

Height of a cardboard box [cm]: 24

Length of a cardboard box [cm]: 43

Volume of a cardboard box [m³]: 0.028896

ADDITIONAL INFORMATION:

- Maximum permissible holder temperature 250°C for BR-GZ10, HLDR-GZ10, HLDR-R7S, for other models - 180°C
- Maximum permissible current for BR-GZ10, HLDR-GZ10, HLDR-G9 - 2A, for HLDR-R7S - 6A, for HLDR-GX5.3 - 5A
- BR-GZ10 equipped with a support