


Ceiling-mounted spotlight fitting

5905339027931



Kanlux VIDİ is a family of simple in their form, diverse spot-beam holders. You can compose diverse lighting sets of them, choosing from among many colours of these aluminium holders.

GENERAL DATA:

Colour: chrome matte

Necessity of using self-shielding lamps: yes

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Replaceable light source: yes

The product is not suitable to be installed on a normally flammable surface: >35W

The product is not suitable to be covered with a heat-insulating material: yes

Light source included: no

Height [mm]: 25

Diameter [mm]: 79

Assembly hole [mm]: Ø60-75

Wire length [m]: 0.12

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC

Maximum power [W]: max 50

Class of protection against electric shock: III

Light source: MR16

Cap: Gx5,3

Ambient temperature range to which the product can be exposed: 5÷25

The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E

Enclosure material: aluminum alloy

Connection type: Free cable ends

Wire diameter [mm²]: 0.75

Lighting-fixture angle regulation: none

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 50

Number of units in the secondary packaging: 1


Number of units in the packaging: 50

Net unit weight [g]: 40

Grammage [g]: 69

Length of a unit pack [cm]: 8.5

Ceiling-mounted spotlight fitting



Width of a unit pack [cm]: 3.5
Height of a unit pack [cm]: 8.5
Weight of a cardboard box [kg]: 3.45
Width of a cardboard box [cm]: 22.5
Height of a cardboard box [cm]: 19.5
Length of a cardboard box [cm] : 45
Volume of a cardboard box [m³]: 0.019744

