# Kanlux

22432 DALLA CT-DTO50-B

Ceiling-mounted spotlight fitting

5905339224323

Kanlux DALLA is a very carefully made holder for installation inside. It has a movable ring, thanks to which you can adjust the light stream. Its shapes and universal colours allow achieving a modern, discrete effect of elegance.

GENERAL DATA:

Colour: black
Necessity of using self-shielding lamps: yes
Place of assembly: Recessed mount in the ceiling
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Replaceable light source: yes
The product is not suitable to be installed on a normally flammable surface: >35W
The product is not suitable to be covered with a heat-insulating material: yes
Light source included: no
Height [mm]: 26
Diameter [mm]: 82
Assembly hole [mm]: Ø70
Wire length [m]: 0.12

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC
Maximum power [W]: max 50
Class of protection against electric shock: III
Light source: MR16
Cap: Gx5,3
Ambient temperature range to which the product can be exposed: 5÷25
The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E
Enclosure material: aluminum alloy
Connection type: Free cable ends
Wire diameter [mm²]: 0.75
Lighting-fixture angle regulation: in one axis
Lighting-fixture angle regulation [°]: 30
IP class: 20

LOGISTIC DATA:

Unit of measurement: unit
Packaging method: 50
Number of units in the secondary packaging: 1
Number of units in the packaging: 50
Net unit weight [g]: 78

EN

Kanlux

22432   DALLA CT-DTO50-B

Ceiling-mounted spotlight fitting

Grammage [g]: 101.8
Length of a unit pack [cm]: 8.5
Width of a unit pack [cm]: 4
Height of a unit pack [cm]: 8.5
Weight of a cardboard box [kg]: 5.09
Width of a cardboard box [cm]: 22.5
Height of a cardboard box [cm]: 19
Length of a cardboard box [cm] : 45
Volume of a cardboard box [m³]: 0.019238