


## 5905339003379









## GENERAL DATA:

Colour: chrome matte Necessity of using self-shielding lamps: yes Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Replaceable light source: yes The product is not suitable to be installed on a normally flammable surface: >35W The product is not suitable to be covered with a heatinsulating material: yes Light source included: no Height [mm]: 44 Diameter [mm]: 100 Assembly hole [mm]: Ø80-90 Wire length [m]: 0.12


## **TECHNICAL DATA:**

Rated voltage [V]: 12 AC; 12 DC Maximum power [W]: max 50 Class of protection against electric shock: III Light source: MR16 Cap: Gx5,3 Ambient temperature range to which the product can be exposed: 5÷25 The fixture is adapted to the light sources of the following energy classes: A++,A+,A,B,C,D,E Enclosure material: steel Connection type: Free cable ends Wire diameter [mm<sup>2</sup>]: 0.75 Lighting-fixture angle regulation: in one axis Lighting-fixture angle regulation [°]: 45 IP class: 20

## LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the secondary packaging: 1 Number of units in the packaging: 50 Net unit weight [g]: 124 Grammage [g]: 160 Length of a unit pack [cm]: 10.5 Width of a unit pack [cm]: 10.5 Height of a unit pack [cm]: 10.5 Weight of a cardboard box [kg]: 8 Width of a cardboard box [cm]: 24.5





Height of a cardboard box [cm]: 23 Length of a cardboard box [cm] : 53.5 Volume of a cardboard box [m<sup>3</sup>]: 0.030147



