

33213 T8 LED GLASSv4 18W-CW

LED light source

5905339332134




















Kanlux T8 LED GLASS is a well-known and proven line of fluorescent lamps based on high-performance LED diodes, which are placed in a milky, glass body, thanks to which they evenly emit light. High-quality workmanship and care for the best-class components are the most important features of Kanlux T8 LED GLASSv4. In addition, these unique LED lamps have a 3-year warranty and a luminous efficacy of up to 160 lumens from Watt.

GENERAL DATA:

Colour: white

Lamp designed for decorative lighting: no

Compatible with a dimmer: no

Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1212 Diameter [mm]: 28 Mercury content: no

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Lamp-power factor: 0.9 Rated power [W]: 18 Lampshade material: glass

Light source: T8 LED **Diode type**: LED SMD

Total rated luminous flux [lm]: 2880 Colour temperature: cold white Colour temperature [K]: 6500 Colour uniformity [SDCM]: ≤6 Colour-rendering index Ra: ≥80

Cap: G13

Rated lamp-service life [h]: 30000 Number of on/off cycles: ≥30000 Rated beam angle [°]: 220 Rated light level [°]: 220

Light source EEI: A++
Lamp rated current [mA]: 87

Luminous efficiency of the lamp [lm/W]: 160

Ignition time [s]: ≤ 0.5

Lamp-heating time to 60% of the full luminous flux [s]:

Negligible

Lamp-heating time to 95% [s]: <2


Lamp premature-failure indicator: <5% po 1000h


Ambient temperature range to which the product can be

exposed: -10÷40

Lamp service life factor after the period of 6000h [%]:

≥90










33213 T8 LED GLASSv4 18W-CW

LED light source





Luminous flux retention factor at the end of rated

service life [%]: ≥70

Luminous flux retention factor after the period of 6000h

[%]: ≥80

Light source shape: liniowa

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 25

Number of units in the secondary packaging: 1

Number of units in the packaging: 25

Net unit weight [g]: 204 Grammage [g]: 295.2

Length of a unit pack [cm]: 126 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 3

Weight of a cardboard box [kg]: 7.38
Width of a cardboard box [cm]: 19.5
Height of a cardboard box [cm]: 20
Length of a cardboard box [cm]: 129
Volume of a cardboard box [m³]: 0.05031

ADDITIONAL INFORMATION:

- One-way fluorescent LED-power supply
- 3 years Warranty under the terms of the warranty statement, available on our website

