


## 33200 ANTEM LED 10W-NW B

LED floodlight

5905339332004



Kanlux ANTEM is a series of LED floodlights. These floodlights are above all easy to connect, and thanks to the integrated junction box you can also avoid unaesthetic cable connections. Kanlux ANTEM LED series provides a wide range of power options, from 10 W to 100 W, as well as versions with and without motion sensors. A milky lampshade with a delicate prism softly disperses light and reduces the glare effect. The version without a motion sensor has a tightness of IP65, while the one with a sensor has a tightness of IP44. The sensor can be adjusted in terms of light duration, light intensity and detection range.

### GENERAL DATA:

**Colour:** black

**Place of assembly:** wall mounted, ceiling mounted, surface mounted

**Place of application:** Indoors and outdoors

**Minimum distance from the illuminated object:** 1m

**Compatible with a dimmer:** no

**Replaceable light source:** no

**Length [mm]:** 101

**Width [mm]:** 35

**Height [mm]:** 125

**Integrated LED light source:** yes

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC

**Rated frequency [Hz]:** 50

**Maximum power [W]:** 10

**Class of protection against electric shock:** I

**Diode type:** LED SMD

**Luminous flux [lm]:** 800

**Colour temperature:** white

**Colour temperature [K]:** 4000

**Colour uniformity [SDCM]:** ≤6

**Colour-rendering index Ra:** ≥80

**Service life [h]:** 15000

**Number of on/off cycles:** ≥10000

**Lighting angle [°]:** 100

**Luminous efficiency of the lamp [lm/W]:** 80

**Ambient temperature range to which the product can be exposed:** -20÷35

**Enclosure material:** aluminum alloy

**Protective glass material:** Tempered glass

## 33200 ANTEM LED 10W-NW B

LED floodlight



**Extension-arm material:** Metal

**Connection type:** Bolt terminal block

**Range of sections of wires used [mm<sup>2</sup>]:** 1-1,5

**The fixture set includes built-in LED's with the following energy classes:** A++,A+,A

**Lamp-heating time [s]:** ≤1

**Lamp-ignition time [s]:** ≤0,5

**The fixture is movable vertically [°]:** 180

**IP class:** 65

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 40

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 40

**Net unit weight [g]:** 214

**Grammage [g]:** 264

**Length of a unit pack [cm]:** 12.5

**Width of a unit pack [cm]:** 4

**Height of a unit pack [cm]:** 13

**Weight of a cardboard box [kg]:** 10.56

**Width of a cardboard box [cm]:** 27

**Height of a cardboard box [cm]:** 28

**Length of a cardboard box [cm]:** 41

**Volume of a cardboard box [m<sup>3</sup>]:** 0.030996

