




DASAR@ 270

Outdoor LED inground fitting, 3000K, round, IP67, symmetrical beam

If you wish to use inground fittings in open spaces or to illuminate your pond, the IP 65 / IP 67 safety class is the important thing. The DASAR@ 270 has the required safety class, and is therefore protected from penetration by dust and water (even if it is occasionally submerged). The inground fitting is round and has symmetric light distribution. Are you looking for amazing light for your outdoor area? This is what you get with the built-in Premium LED of the DASAR@ 270 inground fitting. Of course, the lamp head is tiltable. Impressed? We certainly are! Because we at SLV have done all that we can to ensure that our products complete your lighting solutions for almost 40 years.



TECHNICAL DATA

Item no.:	1002897
Primary nominal voltage	220-240V ~50/60Hz mA/V
Secondary power / secondary voltage	700 mA/V
Vertical tilting range	30 °
Height	20.3 cm
Diameter	27.0 cm
Installation diameter	25.0 cm
Installation depth	19.9 cm
Net weight	5.918 kg
Gross weight	6.504 kg
IP Code	IP 65 / IP 67
Safety class	I
Impact resistance class	IK08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground
Number of through-wires	60
Wattage	30 W
Lumen	2500 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black

Accessories

1002899	Grill Diffusor for DASAR® 270 Outdoor , LED inground fitting with symmetrical beam
---------	--

CRI	>80
Binning	3
LXXBXX data	70/50
Service life	50000 h
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Mechanical loading	2 t
BIG WHITE Page	763

Notes
