

## ToLEDo Retro GLS

ToLEDo RT GLS V4 CL 806LM 827 E27 BL

0027127



### Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating
- Suitable replacement for incandescent and halogen lamps
- Gives same sparkling light effect as incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions



## PRODUCT OVERVIEW

Product name	ToLEDo RT GLS V4 CL 806LM 827 E27 BL
Technology	LED
Watt (Rated) (W)	7
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number SE	8295010
Warranty	3 years
Luminous flux (lm)	806
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Wattage (W)	7
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288271279

## DATA TABLE

### General data

Product name	ToLEDo RT GLS V4 CL 806LM 827 E27 BL
Technology	LED
Watt (Rated) (W)	7
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number SE	8295010
Warranty	3 years

## ToLEDo Retro GLS

ToLEDo RT GLS V4 CL 806LM 827 E27 BL  
0027127

### Optical data

Luminous flux (lm)	806
Luminous flux (Rated) (lm)	806
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	7
Equivalent watt (W)	60
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	3.9
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	7
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	26
Max. Luminaires per 16A C Breaker	41
Max. Luminaires per 20A C Breaker	51

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	60
Weight (kg)	0.039

### Packaging

Single packaging type	Mix blister(20% carton, 80% pl)
Product EAN number	5410288271279
Packaging single length / height (cm)	15.4
Packaging single width (cm)	13.4
Packaging single depth (cm)	8.0
DUN14 (inner)	25410288271273
Units per inner package	6
Packaging inner length / height (cm)	27.2
Packaging inner width (cm)	16.2
Packaging inner depth (cm)	16.8
DUN14 (outer)	15410288271276
Units per outer package	60

## ToLEDo Retro GLS

*ToLEDo RT GLS V4 CL 806LM 827 E27 BL*


0027127

Packaging outer length / height (cm)	84.0
Packaging outer width (cm)	28.4
Packaging outer depth (cm)	32.3

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

## TECHNICAL DRAWINGS



## ToLEDo Retro GLS

ToLEDo RT GLS V4 CL 806LM 827 E27 BL  
0027127

