

UVC Germicidal T5

G6 T5 G5 QUARTZ
0002330



Product features

- The primary application of the Sylvania UV-C lamps is the disinfection and sterilisation. These lamps remain unparalleled in their efficiency for the destruction of bacteria, viruses, mould spores and other micro-organisms.



PRODUCT OVERVIEW

| | |
|-----------------------------|---------------------------|
| Product name | G6 T5 G5 QUARTZ |
| Technology | FLO |
| Watt (Rated) (W) | 6 |
| Lamp shape | Tube, double-ended |
| Cap/Base | G5 |
| Lamp finish | Clear |
| Fixture rating | Open |
| Warranty | 2 years |
| Light colour | UV |
| Wattage (W) | 6 |
| Total power consumption (W) | 6 |
| Product Voltage (V) | 42 |
| Control gear type | Magnetic Low Loss ballast |
| Dimmable | No |
| Average life (Nominal) (h) | 8000 |
| Product EAN number | 5410288023304 |

DATA TABLE

General data

| | |
|---|--------------------|
| Product name | G6 T5 G5 QUARTZ |
| Technology | FLO |
| Watt (Rated) (W) | 6 |
| Lamp shape | Tube, double-ended |
| Cap/Base | G5 |
| Lamp finish | Clear |
| Fixture rating | Open |
| Performance ambient temperature Tq (°C) | 25 |
| Warranty | 2 years |

Optical data

| | |
|--------------|----|
| Light colour | UV |
|--------------|----|

Electrical data

| | |
|--|--|
| | |
|--|--|

UVC Germicidal T5 G6 T5 G5 QUARTZ 0002330

| | |
|---|---------------------------|
| Wattage (W) | 6 |
| Total power consumption (W) | 6 |
| Watt (Rated) - High frequency (W) | 6 |
| Starting time (max) (s) | 10 |
| Warm-up time to 60% of full light (max) (s) | 10 |
| Current (A) | 0.160 |
| Mains voltage (V) | 220-240V~ |
| Product Voltage (V) | 42 |
| Ignition voltage (V) | 300 |
| Control gear required | Yes |
| Control gear type | Magnetic Low Loss ballast |
| Dimmable | No |
| kWh per 1000 hours burning time | 6 |

Lifetime data

| | |
|----------------------------|------|
| Average life (Nominal) (h) | 8000 |
| Average life (Rated) (h) | 8000 |

Physical data

| | |
|-------------------------------------|-------|
| Nominal Product Length (mm) | 218 |
| Nominal Product Diameter (mm) | 15 |
| Max. Length base to base (mm) - A | 212.1 |
| Length base to pin Min-Max (mm) - B | 219.2 |
| Max. Lamp Length (mm) - C/L | 226.3 |
| Weight (kg) | 0.038 |

Packaging

| | |
|---------------------------------------|----------------|
| Single packaging type | Carton |
| Product EAN number | 5410288023304 |
| Packaging single length / height (cm) | 242.0 |
| Packaging single width (cm) | 32.0 |
| Packaging single depth (cm) | 32.0 |
| DUN14 (outer) | 15410288023301 |
| Units per outer package | 30 |
| Packaging outer length / height (cm) | 27.0 |
| Packaging outer width (cm) | 21.2 |
| Packaging outer depth (cm) | 18.3 |

Safety data

| | |
|-------------------------------------|-----------------|
| Lamp mercury content (mg) | 5 |
| Breakage cleaning instructions | applicable |
| Special purpose lamp | Yes |
| Intended purpose | Germicidal UV-C |
| Suitable for household illumination | No |