


Ring for spotlight fittings

5905339278104



The Kanlux ELNIS L is a fixture which consists of two parts forming a whole. It is a combination of two separate elements: the body (the main part) and the casing (the spacer ring), forming a perfectly matched whole. The ELNIS L is a fixture with a 25-mm high casing. The Kanlux ELNIS L is characterised by modern design and very-high quality of workmanship.

### GENERAL DATA:

**Colour:** black/gold

**Necessity of using self-shielding lamps:** yes

**Place of assembly:** Recessed mount in the ceiling

**Place of application:** Indoors

**Minimum distance from the illuminated object:** 0,5m

**Decorative ring without a ceramic frame:** yes

**Replaceable light source:** yes

**The product is not suitable to be covered with a heat-insulating material:** yes

**Light source included:** no

**Height [mm]:** 44

**Diameter [mm]:** 98

**Assembly hole [mm]:** Ø70

### TECHNICAL DATA:

**Rated voltage [V]:** 12 AC; 12 DC; 220-240 AC

**Maximum power [W]:** max 35

**Class of protection against electric shock:** II/III

**Light source:** MR16/PAR16

**Cap:** Gx5,3/GU10

**Ambient temperature range to which the product can be exposed:** 5÷25

**The fixture is adapted to the light sources of the following energy classes:** A++,A+,A,B,C,D,E

**Enclosure material:** aluminum alloy

**Lighting-fixture angle regulation:** none

**IP class:** 20

### LOGISTIC DATA:

**Unit of measurement:** unit

**Packaging method:** 50

**Number of units in the secondary packaging:** 1

**Number of units in the packaging:** 50

**Net unit weight [g]:** 160

**Grammage [g]:** 199.8

**Length of a unit pack [cm]:** 10

**Width of a unit pack [cm]:** 10

Ring for spotlight fittings



**Height of a unit pack [cm]: 5**

**Weight of a cardboard box [kg]: 9.99**

**Width of a cardboard box [cm]: 21**

**Height of a cardboard box [cm]: 26.5**

**Length of a cardboard box [cm] : 52**

**Volume of a cardboard box [m<sup>3</sup>]: 0.028938**