


Ring for spotlight fittings

5905339331656



GENERAL DATA:

Colour: black

Place of assembly: Recessed mount in the ceiling

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Decorative ring without a ceramic frame: yes

Replaceable light source: yes

The product is not suitable to be covered with a heat-insulating material: yes

Light source included: no

Height [mm]: 42

Diameter [mm]: 107

Assembly hole [mm]: Ø95

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC

Maximum power [W]: 10

Class of protection against electric shock: II/III

Light source: MR16/PAR16

Cap: GX5.3/GU10

Ambient temperature range to which the product can be exposed: 5÷25

The fixture is adapted to the light sources of the following energy classes: A++,A+,A

Enclosure material: aluminum alloy

Lighting-fixture angle regulation: in one axis

Lighting-fixture angle regulation [°]: 20

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 50

Number of units in the packaging: 50

Net unit weight [g]: 128

Grammage [g]: 186

Length of a unit pack [cm]: 12

Width of a unit pack [cm]: 5

Height of a unit pack [cm]: 12

Weight of a cardboard box [kg]: 9.3

Width of a cardboard box [cm]: 28.5

Height of a cardboard box [cm]: 26.5

Length of a cardboard box [cm]: 61.5

Volume of a cardboard box [m³]: 0.046448

Ring for spotlight fittings

