

Ring for spotlight fittings


5905339331663













GENERAL DATA:

Colour: white Place of assembly: Recessed mount in the ceiling Place of application: Indoors Minimum distance from the illuminated object: 0,5m Decorative ring without a ceramic frame: yes Replaceable light source: yes The product is not suitable to be covered with a heatinsulating material: yes Light source included: no Height [mm]: 42 Diameter [mm]: 107 Assembly hole [mm]: Ø95

TECHNICAL DATA:

Rated voltage [V]: 12 AC; 12 DC; 220-240 AC Maximum power [W]: 10 Class of protection against electric shock: II/III Light source: MR16/PAR16 Cap: GX5.3/GU10 Ambient temperature range to which the product can be exposed: 5÷25 The fixture is adapted to the light sources of the following energy classes: A++,A+,A Enclosure material: aluminum alloy Lighting-fixture angle regulation: in one axis Lighting-fixture angle regulation [°]: 20 IP class: 20

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 50 Number of units in the packaging: 50 Net unit weight [g]: 128 Grammage [g]: 186 Length of a unit pack [cm]: 12 Width of a unit pack [cm]: 5 Height of a unit pack [cm]: 12 Weight of a cardboard box [kg]: 9.3 Width of a cardboard box [kg]: 9.3 Width of a cardboard box [cm]: 28.5 Height of a cardboard box [cm]: 26.5 Length of a cardboard box [cm]: 61.5 Volume of a cardboard box [m³]: 0.046448



Ring for spotlight fittings



