


Ceiling-mounted spotlight fitting

5905339243621



Kanlux SONOR GU10 is a surface-mounted luminaire with an additional LED strip. Thanks to two independent light sources, this lamp can shine in three different ways. With only the LED strip shining (ceiling effect, ideal as evening light), only the bulb in the luminaire shining (thanks to the plastic lampshade, the luminaire looks like an integrated one), while the third variant is to light both light sources simultaneously and make full use of its possibilities. For best effect, we recommend the use of light bulbs with a colour temperature of 3000 K. For Kanlux SONOR lamps, we recommend the use of a two-group (double) switch in order to take full advantage of the possibilities of lighting these lamps.

GENERAL DATA:

Colour: black

Place of assembly: ceiling mounted

Place of application: Indoors

Minimum distance from the illuminated object: 0,5m

Compatible with a dimmer: no

Replaceable light source: yes

The product is not suitable to be covered with a heat-insulating material: yes

Light source included: no

Height [mm]: 120

Diameter [mm]: 100

Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Maximum power [W]: max 10

Rated power (LED) [W]: 4

Class of protection against electric shock: I

Lampshade material: plastic

Light source: PAR16

Diode type: LED SMD

Luminous flux [lm]: 100

Colour temperature: Warm white

Colour temperature [K]: 3000

Colour uniformity [SDCM]: ≤6

Colour-rendering index Ra: ≥80

Cap: GU10

Service life [h]: 20000

Number of on/off cycles: ≥15000

Ambient temperature range to which the product can be exposed: 5÷25

The fixture is adapted to the light sources of the following energy classes: A++,A+,A

24362 SONOR GU10 CO-B WW

Ceiling-mounted spotlight fitting



Enclosure material: aluminum alloy

Connection type: Self-clamping block

Range of sections of wires used [mm²]: 1,5-2,5

The fixture set includes built-in LED's with the following energy classes: A++,A+,A

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 20

LOGISTIC DATA:

Unit of measurement: unit

Packaging method: 20

Number of units in the packaging: 20

Net unit weight [g]: 480

Grammage [g]: 559.5

Length of a unit pack [cm]: 10.5

Width of a unit pack [cm]: 10.5

Height of a unit pack [cm]: 14

Weight of a cardboard box [kg]: 11.19

Width of a cardboard box [cm]: 23

Height of a cardboard box [cm]: 30

Length of a cardboard box [cm] : 54

Volume of a cardboard box [m³]: 0.03726