


Halide light source

5905339104182



The designed halogen bulbs are intended for lamps and halopaks with R7s thread. Available power from 1000W to 1500W. They are meant for horizontal work.

### GENERAL DATA:

**Height [mm]:** 189  
**Diameter [mm]:** 12  
**Mercury content:** no

### TECHNICAL DATA:

**Rated voltage [V]:** 220-240 AC  
**Rated frequency [Hz]:** 50/60  
**Rated power [W]:** 1000  
**Lampshade material:** glass  
**Total rated luminous flux [lm]:** 16000  
**Colour temperature:** Warm white  
**Colour temperature [K]:** 2700  
**Cap:** R7s  
**Rated lamp-service life [h]:** 2000  
**Number of on/off cycles:**  $\geq 8000$   
**Light source EEL:** D  
**Annual power consumption [kWh/1000h]:** 1000  
**Luminous efficiency of the lamp [lm/W]:** 16  
**Ignition time [s]:**  $\leq 0,1$   
**Lamp-heating time to 60% of the full luminous flux [s]:**  $< 1$   
**J light-bulb equivalent [W]:** 1063

### LOGISTIC DATA:

**Unit of measurement:** unit  
**Packaging method:** 50  
**Number of units in the secondary packaging:** 50  
**Number of units in the packaging:** 500  
**Net unit weight [g]:** 14  
**Grammage [g]:** 27.2  
**Length of a unit pack [cm]:** 2.5  
**Width of a unit pack [cm]:** 2.5  
**Height of a unit pack [cm]:** 21  
**Weight of a cardboard box [kg]:** 13.6  
**Width of a cardboard box [cm]:** 25  
**Height of a cardboard box [cm]:** 29  
**Length of a cardboard box [cm]:** 66  
**Volume of a cardboard box [m<sup>3</sup>]:** 0.04785

### ADDITIONAL INFORMATION:

Halide light source



- designed for horizontal operation, allowable deflection of working position  $\pm 4^\circ$

