Kanlux 26065 T8 LED GLASSv3 18W-CW

LED light source

5905339260659







6

WHIT Salari

Ø28





23



The Kanlux T8 LED GLASS is a well-known and proven line of fluorescent lamps utilising high-performance SMD LED's in a milky-coloured glass body. The high guality of workmanship and the care taken over choosing the best-quality components are the most-important features of the T8 LED GLASSv3.

GENERAL DATA:

Colour: white Lamp designed for decorative lighting: no Compatible with a dimmer: no Power supply of T8 LED fluorescent lamps: Unilateral Height [mm]: 1210 Diameter [mm]: 28 Mercury content: no


TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50/60 Lamp-power factor: 0.9 Rated power [W]: 18 Lampshade material: glass Light source: T8 LED Diode type: LED SMD Total rated luminous flux [lm]: 2520 **Colour temperature**: cold white Colour temperature [K]: 6500 **Colour uniformity [SDCM]**: ≤ 6 **Colour-rendering index Ra**: ≥80 **Cap**: G13 Rated lamp-service life [h]: 25000 Number of on/off cycles: ≥ 15000 Rated beam angle [°]: 250 Rated light level [°]: 250 Light source EEI: A++ Lamp rated current [mA]: 79 Annual power consumption [kWh/1000h]: 18 Luminous efficiency of the lamp [lm/W]: 140 Ignition time [s]: $\leq 0,5$ Lamp-heating time to 60% of the full luminous flux [s]: Negligible Lamp-heating time to 95% [s]: <2 Lamp premature-failure indicator: <5% po 1000h Ambient temperature range to which the product can be exposed: -10÷40 Lamp service life factor after the period of 6000h [%]:



Kanlux 26065 T8 LED GLASSv3 18W-CW

LED light source







≥90


Luminous flux retention factor at the end of rated service life [%]: \geq 70 Luminous flux retention factor after the period of 6000h [%]: \geq 80 Light source shape: liniowa

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 25 Number of units in the secondary packaging: 1 Number of units in the packaging: 25 Net unit weight [g]: 208 Grammage [g]: 308 Length of a unit pack [cm]: 125.5 Width of a unit pack [cm]: 3 Height of a unit pack [cm]: 3 Weight of a cardboard box [kg]: 7.7 Width of a cardboard box [kg]: 7.7 Width of a cardboard box [cm]: 19.5 Height of a cardboard box [cm]: 19 Length of a cardboard box [cm]: 129 Volume of a cardboard box [m³]: 0.047795

ADDITIONAL INFORMATION:

• One-way fluorescent LED-power supply



Kanlux 26065 T8 LED GLASSv3 18W-CW

LED light source

KANLUX S.A. (kat 26065) T8 LED GLASSv3 18W CW / LDC (Polar) Luminaire: KANLUX S.A. (kat 26065) T8 LED GLASSv3 18W CW Lamps: 1 x T8 LED GLASSv3 18W-CW 135° 150° 165° 180° 165 150° 135° 160 120 120° 120° 80 105° 105° 90° 909 75° 75° 60 60° 15° 45° 45 cd/klm C0 - C180 C90 - C270