



- ▶ casing: plastic / conducting bus bars: copper
- ▶ Gehäuse: Kunststoff / Leiterschienen: Kupfer

Kanlux	Kanlux	Un		[g]
BBU12/1	02155	230/400V~	-/-/500	52
BBU56/1	02157	230/400V~	-/-/100	265
BBU12/3	02156	400V~	-/-/200	120
BBU54/3	02158	400V~	-/-/30	735



for connection of modular equipment mono-nominal poles / compliance with EN60439-1/EN60439-2 standards / model BBU12/1 is used for connecting the maximum of twelve single-phase devices; model BBU56/1 is used for connecting the maximum of fifty six single-phase devices / model BBU12/3 is used for connecting the maximum of four three-phase devices, model BBU54/3 is used for connecting the maximum of eighteen three-phase devices zur Verbindung gleichnamiger Pole der Modulargeräte / Konformität mit den Normen EN60439-1/EN60439-2 / das Modell BBU12/1 dient zur Verbindung von maximal zwölf Einphasengeräten, Modell BBU56/1 dient zur Verbindung von maximal sechsfünfzig Einphasengeräten / das Modell BBU12/3 dient zur Verbindung von maximal vier Dreiphasengeräten, Modell BBU54/3 dient zur Verbindung von maximal achtzehn Dreiphasengeräten

